





Local Government Energy Audit Report

Marsee Center

October 3, 2023

Prepared for:

Princeton Charter School

100 Bunn Dr

Princeton, New Jersey 08540

Prepared by:

TRC

317 George Street

New Brunswick, New Jersey 08901





Disclaimer

The goal of this audit report is to identify potential energy efficiency opportunities and help prioritize specific measures for implementation. Most energy conservation measures have received preliminary analysis of feasibility that identifies expected ranges of savings and costs. This level of analysis is usually considered sufficient to establish a basis for further discussion and to help prioritize energy measures.

TRC reviewed the energy conservation measures and estimates of energy savings for technical accuracy. Actual, achieved energy savings depend on behavioral factors and other uncontrollable variables and, therefore, estimates of final energy savings are not guaranteed. TRC and the New Jersey Board of Public Utilities (NJBPU) shall in no event be liable should the actual energy savings vary.

TRC bases estimated material and labor costs primarily on RS Means cost manuals as well as on our experience at similar facilities. This approach is based on standard cost estimating manuals and is vendor neutral. Cost estimates include material and labor pricing associated with one for one equipment replacements. Cost estimates do not include demolition or removal of hazardous waste. The actual implementation costs for energy savings projects are anticipated to be significantly higher based on the specific conditions at your site(s). We strongly recommend that you work with your design engineer or contractor to develop actual project costs for your specific scope of work for the installation of high efficiency equipment. We encourage you to obtain multiple estimates when considering measure installations. Actual installation costs can vary widely based on selected products and installers. TRC and NJBPU do not guarantee cost estimates and shall in no event be held liable should actual installed costs vary from these material and labor estimates.

Incentive values provided in this report are estimated based on previously run state efficiency programs. Incentive levels are not guaranteed. The NJBPU reserves the right to extend, modify, or terminate programs without prior notice. Please review all available utility program incentives and eligibility requirements prior to selecting and installing any energy conservation measures.

The customer and their respective contractor(s) are responsible to implement energy conservation measures in complete conformance with all applicable local, state, and federal requirements.

Copyright ©2023 TRC. All rights reserved.

Reproduction or distribution of the whole, or any part of the contents of this document without written permission of TRC is prohibited. Neither TRC nor any of its employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any data, information, method, product or process disclosed in this document, or represents that its use will not infringe upon any privately-owned rights, including but not limited to, patents, trademarks or copyrights.





Table of Contents

1	Execu	utive Summary	1
	1.1	Planning Your Project	4
	Picl	k Your Installation Approach	4
	Opt	tions from Your Utility Company	4
		scriptive and Custom Rebates	
		ect Install	
	_	gineered Solutionstions from New Jersey's Clean Energy Program	
•			
2		ng Conditions	
	2.1	Site Overview	
	2.2	Building Occupancy	
	2.3	Building Envelope	
	2.4	Lighting Systems	
	2.5	Air Handling Systems	8
		itary Electric HVAC Equipment	
	Pac	kaged Units	8
	2.6	Steam Heating Systems	9
	2.7	Plug Load and Vending Machines	9
	2.8	Water-Using Systems	9
3	Energ	gy Use and Costs	10
	3.1	Electricity	
	3.2	No. 2 Fuel Oil	13
	3.3	Benchmarking	14
	Tra	cking Your Energy Performance	15
4	Energ	gy Conservation Measures	16
	4.1	Lighting	18
	ECN	M 1: Install LED Fixtures	
		VI 2: Retrofit Fixtures with LED Lamps	
	4.2	Lighting Controls	
		VI 3: Install Occupancy Sensor Lighting Controls	
		Domestic Water Heating	
	4.3	•	
_		M 4: Install Low-Flow DHW Devices	
5	Energ	gy Efficient Best Practices	21
		ergy Tracking with ENERGY STAR Portfolio Manager	
	_	hting Maintenance	
		ns to Reduce Cooling Load	
		System Evaporator/Condenser Coil Cleaningler Maintenance	
		ter Heater Maintenance	
		ter Conservation	






	Proc	curement Strategies	23
6	On-sit	e Generation	24
	6.1 6.2	Solar Photovoltaic Combined Heat and Power	
7	Electri	ic Vehicles (EV)	28
	7.1	Electric Vehicle Charging	28
8	Projec	ct Funding and Incentives	30
	8.1	Utility Energy Efficiency Programs	31
	Dire	ccriptive and Customct Installineered Solutions	31
	8.2	New Jersey's Clean Energy Programs	33
		e Energy Users	
	Succ	nbined Heat and Power	35
9 10	•	t Developmenty Purchasing and Procurement Strategies	
	10.1 10.2	Retail Electric Supply OptionsRetail Natural Gas Supply Options	
Αp	pendix	A: Equipment Inventory & Recommendations	
•	•	B: ENERGY STAR Statement of Energy Performance	





1 EXECUTIVE SUMMARY

The New Jersey Board of Public Utilities (NJBPU) has sponsored this Local Government Energy Audit (LGEA) report for Marsee Center. This report provides you with information about your facility's energy use, identifies energy conservation measures (ECMs) that can reduce your energy use, and provides information and assistance to help make changes in your facility. TRC conducted this study as part of a comprehensive effort to assist New Jersey school districts and local governments in controlling their energy costs and to help protect our environment by reducing statewide energy consumption.






Figure 1 - Energy Use by System






POTENTIAL IMPROVEMENTS



This energy audit considered a range of potential energy improvements in your building. Costs and savings will vary between improvements. Presented below are two potential scopes of work for your consideration.


Scenario 1: Full Package (All Evaluated Measures)

Installation Cost	\$7,229	Э		
Potential Rebates & Incenti	ives ¹ \$1,101	1		
Annual Cost Savings	\$1,306	5		
Annual Energy Savings	Electricity: 9,715 kWh			
Ailliual Ellergy Saviligs	No. 2 Fuel Oil: -11 Gallon			
Greenhouse Gas Emission S	Savings 5 Tons	S		
Simple Payback	4.7 Years	S		
Site Energy Savings (All Util	ities) 13%	6		



Scenario 2: Cost Effective Package²

Installation Cost		\$7,229		
Potential Rebates & Incenti	ves	\$1,101		
Annual Cost Savings		\$1,306		
Annual Engrav Savings	Electricity: 9,715 kWh			
Annual Energy Savings	No. 2 Fuel Oil: -11 Gallor			
Greenhouse Gas Emission S	Savings	5 Tons		
Simple Payback		4.7 Years		
Site Energy Savings (all utili	ties)	13%		



On-site Generation Potential

Photovoltaic	None
Combined Heat and Power	None

¹ Incentives are based on previously run state rebate programs. Contact your utility provider for current program incentives that may apply.

² A cost-effective measure is defined as one where the simple payback does not exceed two-thirds of the expected proposed equipment useful life. Simple payback is based on the net measure cost after potential incentives.





#	Energy Conservation Measure	Cost Effective?	Annual Electric Savings (kWh)	Peak Demand Savings (kW)		Annual Energy Cost Savings (\$)	Estimated M&L Cost (\$)	Estimated Incentive (\$)*	Estimated Net M&L Cost (\$)	Simple Payback Period (yrs)**	CO ₂ e Emissions Reduction (lbs)
Lighting Upgrades			8,669	1.6	-2	\$1,153	\$4,777	\$778	\$3,999	3.5	8,451
ECM 1	Install LED Fixtures	Yes	4,599	0.0	0	\$642	\$2,824	\$300	\$2,524	3.9	4,631
ECM 2	Retrofit Fixtures with LED Lamps	Yes	4,070	1.6	-2	\$511	\$1,953	\$478	\$1,475	2.9	3,820
Lighting	Lighting Control Measures			0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982
ECM 3	Install Occupancy Sensor Lighting Controls	Yes	1,046	0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982
Domest	ic Water Heating Upgrade		0	0.0	1	\$21	\$22	\$8	\$14	0.6	105
ECM 4	Install Low-Flow DHW Devices	Yes	0	0.0	1	\$21	\$22	\$8	\$14	0.6	105
	TOTALS (COST EFFECTIVE MEASURES)			2.0	-1	\$1,306	\$7,229	\$1,101	\$6,128	4.7	9,538
	TOTALS (ALL MEASURES)		9,715	2.0	-1	\$1,306	\$7,229	\$1,101	\$6,128	4.7	9,538

^{* -} All incentives presented in this table are included as placeholders for planning purposes and are based on previously run state rebate programs. Contact your utility provider for details on current programs.

Figure 2 – Evaluated Energy Improvements

For more detail on each evaluated energy improvement and a break out of cost-effective improvements, see Section 4: Energy Conservation Measures.

^{** -} Simple Payback Period is based on net measure costs (i.e. after incentives).





1.1 Planning Your Project

Careful planning makes for a successful energy project. When considering this scope of work, you will have some decisions to make, such as:

- ♦ How will the project be funded and/or financed?
- Is it best to pursue individual ECMs, groups of ECMs, or use a comprehensive approach where all ECMs are installed together?
- Are there other facility improvements that should happen at the same time?

Pick Your Installation Approach

Utility-run energy efficiency programs and New Jersey's Clean Energy Programs, give you the flexibility to do a little or a lot. Rebates, incentives, and financing are available to help reduce both your installation costs and your energy bills. If you are planning to take advantage of these programs, make sure to review incentive program guidelines before proceeding. This is important because in most cases you will need to submit applications for the incentives <u>before</u> purchasing materials or starting installation.

Options from Your Utility Company

Prescriptive and Custom Rebates

For facilities wishing to pursue only selected individual measures (or planning to phase implementation of selected measures over multiple years), incentives are available through the Prescriptive and Custom Rebates program. To participate, you can use internal resources or an outside firm or contractor to perform the final design of the ECM(s) and install the equipment. Program pre-approval may be required for some incentives. Contact your utility company for more details prior to project installation.

Direct Install

The Direct Install program provides turnkey installation of multiple measures through an authorized contractor. This program can provide incentives up to 70% or 80% of the cost of selected measures. A Direct Install contractor will assess and verify individual measure eligibility and perform the installation work. The Direct Install program is available to sites with an average peak demand of less than 200 kW.

Engineered Solutions

The Engineered Solutions program provides tailored energy-efficiency assistance and turnkey engineering services to municipalities, universities, schools, hospitals, and healthcare facilities (MUSH), non-profit entities, and multifamily buildings. The program provides all professional services from audit, design, construction administration, to commissioning and measurement and verification for custom whole-building energy-efficiency projects. Engineered Solutions allows you to install as many measures as possible under a single project as well as address measures that may not qualify for other programs.

For more details on these programs please contact your utility provider.





Options from New Jersey's Clean Energy Program

Financing and Planning Support with the Energy Savings Improvement Program (ESIP)

For larger facilities with limited capital availability to implement ECMs, project financing may be available through the ESIP. Supported directly by the NJBPU, ESIP provides government agencies with project development, design, and implementation support services, as well as attractive financing for implementing ECMs. You have already taken the first step as an LGEA customer, because this report is required to participate in ESIP.

Resiliency with Return on Investment through Combined Heat and Power (CHP)

The CHP program provides incentives for combined heat and power (i.e., cogeneration) and waste heat to power projects. Combined heat and power systems generate power on-site and recover heat from the generation system to meet on-site thermal loads. Waste heat to power systems use waste heat to generate power. You will work with a qualified developer who will design a system that meets your building's heating and cooling needs.

Successor Solar Incentive Program (SuSI)

New Jersey is committed to supporting solar energy. Solar projects help the state reach the renewable goals outlined in the state's Energy Master Plan. The SuSI program is used to register and certify solar projects in New Jersey. Rebates are not available, but certified solar projects are able to earn one SREC II (Solar Renewable Energy Certificates II) for each megawatt-hour of solar electricity produced from a qualifying solar facility.

Ongoing Electric Savings with Demand Response

The Demand Response Energy Aggregator program reduces electric loads at commercial facilities when wholesale electricity prices are high or when the reliability of the electric grid is threatened due to peak power demand. By enabling commercial facilities to reduce electric demand during times of peak demand, the grid is made more reliable, and overall transmission costs are reduced for all ratepayers. Curtailment service providers provide regular payments to medium and large consumers of electric power for their participation in demand response (DR) programs. Program participation is voluntary, and facilities receive payments regardless of whether they are called upon to curtail their load during times of peak demand.

Large Energy User Program (LEUP)

LEUP is designed to promote self-investment in energy efficiency. It incentivizes owners/users of buildings to upgrade or install energy conserving measures in existing buildings to help offset the capital costs associated with the project. The efficiency upgrades are customized to meet the requirements of the customers' existing facilities, while advancing the State's energy efficiency, conservation, and greenhouse gas reduction goals.

For more details on these programs please visit New Jersey's Clean Energy Program website.







2 EXISTING CONDITIONS

The New Jersey Board of Public Utilities (NJBPU) has sponsored this Local Government Energy Audit (LGEA) report for Marsee Center. This report provides information on how your facility uses energy, identifies energy conservation measures (ECMs) that can reduce your energy use, and provides information and assistance to help you implement the ECMs.

TRC conducted this study as part of a comprehensive effort to assist New Jersey educational and local government facilities in controlling energy costs and protecting our environment by offering a wide range of energy management options and advice.

2.1 Site Overview

On May 8, 2023, TRC performed an energy audit at Marsee Center located in Princeton, New Jersey. TRC met with Patrick Byrne to review the facility operations and help focus our investigation on specific energy-using systems.

Marsee Center is a 2-story, 3,240 square foot building built in 1850. Spaces include offices, corridors, meeting room, restrooms, stairwells, and basement mechanical space.

2.2 Building Occupancy

The facility is occupied Monday through Friday during regular business hours. Janitorial services are performed after hours.

Building Name	Weekday/Weekend	Operating Schedule		
Marsee Center	Weekday	7:00 AM - 6:00 PM		
iviarsee Ceriter	Weekend	Varied		

Figure 3 - Building Occupancy Schedule

2.3 Building Envelope

Wood frame structure clad with vinyl siding supports a pitched roof with a wood deck covered with asphalt shingles. Roof encloses unconditioned space. The thermal barrier is between this space and the conditioned space below.





Building Envelope





Most of the windows are double glazed and have aluminum frames with a thermal break. The glass-to-frame seals are in fair condition. The operable window weather seals are in fair condition, showing little evidence of excessive wear. Exterior doors have aluminum frames and are in fair condition with undamaged door seals. Degraded window and door seals increase drafts and outside air infiltration.







Exterior Doors and Window

2.4 Lighting Systems

The primary interior lighting system uses 32-Watt linear fluorescent T8 lamps. Fixture types include 2-lamp, 4-foot-long surface mounted fixtures. Typically, T8 fluorescent lamps use electronic ballasts.

Additionally, there are some compact fluorescent lamps (CFL) and LED lamps. Most fixtures are in fair condition. Interior lighting levels were generally sufficient.







Linear Surface Mounted, Vanity, and Surface Mounted Fixtures

Lighting fixtures are controlled by wall switches.



Wall Switch





The exterior has halogen incandescent flood lamps around the building. They are controlled by a photocell.



Flood Light Fixture

2.5 Air Handling Systems

Unitary Electric HVAC Equipment

Offices use window air conditioning (AC) units. These vary in capacity between 0.42 and 0.75 tons. The units are in fair condition. They range in efficiency between 10.7 EER to 12.5 EER. They are not ENERGY STAR labeled.







Window AC Units

Packaged Units

Rented space is served with a packaged terminal heat pump (PTHP) unit controlled by local controls. It has an EER of 9 and a heating capacity of 24 MBh and 2-ton cooling capacity.





Packaged Terminal Heat Pump





2.6 Steam Heating Systems

A Weil-McLain 174 MBh oil-fired steam boiler serves the building heating load and domestic hot water needs. The burners are non-modulating with a nominal efficiency of 75 percent. It is in fair condition. Domestic hot water is produced with a steam to water heat exchanger. A manual tempering valve controls the supply water temperature. There is a service contract in place.







Steam Boiler and Oil-Fired Burner

2.7 Plug Load and Vending Machines

You may wish to consider paying particular attention to minimizing your plug load usage. This report makes suggestions for ECMs in this area as well as energy efficient best practices.

There are approximately 10 computer workstations throughout the facility. Plug loads include general cafe and office equipment. There are two mini refrigerators in the kitchenette.







Desktop, Mini Refrigerators, and Toaster Oven/Microwave

2.8 Water-Using Systems

There are 2 restrooms with toilets and sinks. Faucet flow rates are at 1.8 gallons per minute (gpm) or higher.







Kitchen and Lavatory Sinks






3 ENERGY USE AND COSTS

Twelve months of utility billing data are used to develop annual energy consumption and cost data. This information creates a profile of the annual energy consumption and energy costs.

Utility Summary									
Fuel	Usage	Cost							
Electricity	26,238 kWh	\$3,663							
No. 2 Fuel Oil	1,168 Gallons	\$5,414							
Total	\$9,077								



An energy balance identifies and quantifies energy use in your various building systems. This can highlight areas with the most potential for improvement. This energy balance was developed using calculated energy use for each of the end uses noted in the figure.

The energy auditor collects information regarding equipment operating hours, capacity, efficiency, and other operational parameters from facility staff, drawings, and on-site observations. This information is used as the inputs to calculate the existing conditions energy use for the site. The calculated energy use is then compared to the historical energy use and the initial inputs are revised, as necessary, to balance the calculated energy use to the historical energy use.









Figure 4 - Energy Balance





3.1 Electricity

PSE&G delivers electricity under rate class.



Electric Billing Data										
Period Ending	Days in Period Electric Usage (kWh)		Demand (kW)	Demand Cost	Total Electric Cost					
2/11/22	29	3,420	10	\$38	\$325					
3/15/22	32	1,788	9	\$35	\$243					
4/13/22	29	3,024	7	\$29	\$350					
5/13/22	30	1,236	6	\$23	\$208					
6/14/22	32	1,392	6	\$89	\$279					
7/14/22	30	1,476	7	\$102	\$301					
8/15/22	32	2,304	9	\$132	\$398					
9/13/22	29	1,968	8	\$123	\$344					
10/12/22	29	1,548	9	\$42	\$225					
11/10/22	29	1,788	7	\$30	\$230					
12/13/22	33	3,126	9	\$41	\$361					
1/13/23	31	3,168	8	\$37	\$400					
Totals	365	26,238	10	\$721	\$3,663					
Annual	365	26,238	10	\$721	\$3,663					

Notes:


- Peak demand of 10 kW occurred in January '22.
- Average demand over the past 12 months was 8 kW.
- The average electric cost over the past 12 months was \$0.140/kWh, which is the blended rate
 that includes energy supply, distribution, demand, and other charges. This report uses this
 blended rate to estimate energy cost savings.





3.2 No. 2 Fuel Oil

Valley Oil delivers no. 2 fuel oil to the project site.



No. 2 Fuel Oil Billing Data								
Period Ending	Days in Usage (Gallons)		Fuel Cost					
1/1/22	31	168	\$603					
2/1/22	31	265	\$1,034					
3/1/22	28	146	\$742					
4/1/22	31	0	\$0					
5/1/22	30	0	\$0					
6/1/22	31	128	\$754					
7/1/22	30	0	\$0					
8/1/22	31	0	\$0					
9/1/22	31	0	\$0					
10/1/22	30	74	\$417					
11/1/22	31	186	\$929					
12/1/22	30	203	\$935					
Totals	365	1,168	\$5,414					
Annual	365	1,168	\$5,414					

Notes:

- The average no. 2 fuel oil cost for the past 12 months is \$4.633/Gallon, which is the blended rate used throughout the analysis.
- Fuel deliveries do not necessarily correspond to periods of use.





3.3 Benchmarking

Your building was benchmarked using the United States Environmental Protection Agency's (EPA) *Portfolio Manager®* software. Benchmarking compares your building's energy use to that of similar buildings across the country, while neutralizing variations due to location, occupancy, and operating hours. Some building types can be scored with a 1-100 ranking of a building's energy performance relative to the national building market. A score of 50 represents the national average and a score of 100 is best.

This ENERGY STAR benchmarking score provides a comprehensive snapshot of your building's energy performance. It assesses the building's physical assets, operations, and occupant behavior, which is compiled into a quick and easy-to-understand score.

Benchmarking Score

29

This building performs or below the national average. This report contains suggestions about how to improve building performance and reduce energy costs.




Figure 5 - Energy Use Intensity Comparison³

Energy use intensity (EUI) measures energy consumption per square foot and is the standard metric for comparing buildings' energy performance. A lower EUI means better performance and less energy consumed. Several factors can cause a building to vary from typical energy usage. Local weather conditions, building age and insulation levels, equipment efficiency, daily occupancy hours, changes in occupancy throughout the year, equipment operating hours, and occupant behavior all contribute to a building's energy use and the benchmarking score.

_

³ Based on all evaluated ECMs





Tracking Your Energy Performance

Keeping track of your energy use on a monthly basis is one of the best ways to keep energy costs in check. Update your utility information in Portfolio Manager regularly, so that you can keep track of your building's performance.

We have created a Portfolio Manager account for your facility and have already entered the monthly utility data shown above for you. Account login information for your account will be sent via email.

Free online training is available to help you use ENERGY STAR Portfolio Manager to track your building's performance at: https://www.energystar.gov/buildings/training.

For more information on ENERGY STAR and Portfolio Manager, visit their website.





4 ENERGY CONSERVATION MEASURES

The goal of this audit report is to identify and evaluate potential energy efficiency improvements and provide information about the cost effectiveness of those improvements. Most energy conservation measures have received preliminary analysis of feasibility, which identifies expected ranges of savings. This level of analysis is typically sufficient to demonstrate project cost-effectiveness and help prioritize energy measures.

Calculations of energy use and savings are based on the current version of the *New Jersey's Clean Energy Program Protocols to Measure Resource Savings*, which is approved by the NJBPU. Further analysis or investigation may be required to calculate more precise savings based on specific circumstances.

Operation and maintenance costs for the proposed new equipment will generally be lower than the current costs for the existing equipment—especially if the existing equipment is at or past its normal useful life. We have conservatively assumed there to be no impact on overall maintenance costs over the life of the equipment.

Financial incentives in this report are based on the previously run state rebate program SmartStart, which has been retired. Now, all investor-owned gas and electric utility companies are offering complementary energy efficiency programs directly to their customers. Some measures and proposed upgrades may be eligible for higher incentives than those shown below. The incentives in the summary tables should be used for high-level planning purposes. To verify incentives, reach out to your utility provider or visit the NJCEP website for more information.

For a detailed list of the locations and recommended energy conservation measures for all inventoried equipment, see Appendix A: Equipment Inventory & Recommendations.





#	Energy Conservation Measure	Cost Effective?	Annual Electric Savings (kWh)	Peak Demand Savings (kW)	Annual Fuel Savings (MMBtu)	Annual Energy Cost Savings (\$)	Estimated M&L Cost (\$)	Estimated Incentive (\$)*	Estimated Net M&L Cost (\$)	-	CO ₂ e Emissions Reduction (lbs)
Lighting Upgrades			8,669	1.6	-2	\$1,153	\$4,777	\$778	\$3,999	3.5	8,451
ECM 1 Install LED Fixtures Ye		Yes	4,599	0.0	0	\$642	\$2,824	\$300	\$2,524	3.9	4,631
ECM 2	Retrofit Fixtures with LED Lamps	Yes	4,070	1.6	-2	\$511	\$1,953	\$478	\$1,475	2.9	3,820
Lighting Control Measures			1,046	0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982
ECM 3	Install Occupancy Sensor Lighting Controls	Yes	1,046	0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982
Domestic Water Heating Upgrade		0	0.0	1	\$21	\$22	\$8	\$14	0.6	105	
ECM 4	Install Low-Flow DHW Devices	Yes	0	0.0	1	\$21	\$22	\$8	\$14	0.6	105
	TOTALS				-1	\$1,306	\$7,229	\$1,101	\$6,128	4.7	9,538

^{* -} All incentives presented in this table are included as placeholders for planning purposes and are based on previously run state rebate programs. Contact your utility provider for details on current programs.

Figure 6 – All Evaluated ECMs

#	Energy Conservation Measure	Annual Electric Savings (kWh)	Peak Demand Savings (kW)		Annual Energy Cost Savings (\$)	Estimated M&L Cost (\$)	Estimated Incentive (\$)*	Estimated Net M&L Cost (\$)		CO ₂ e Emissions Reduction (lbs)
Lighting Upgrades		8,669	1.6	-2	\$1,153	\$4,777	\$778	\$3,999	3.5	8,451
ECM 1	Install LED Fixtures	4,599	0.0	0	\$642	\$2,824	\$300	\$2,524	3.9	4,631
ECM 2	Retrofit Fixtures with LED Lamps	4,070	1.6	-2	\$511	\$1,953	\$478	\$1,475	2.9	3,820
Lighting Control Measures		1,046	0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982
ECM 3	Install Occupancy Sensor Lighting Controls	1,046	0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982
Domestic Water Heating Upgrade		0	0.0	1	\$21	\$22	\$8	\$14	0.6	105
ECM 4 Install Low-Flow DHW Devices		0	0.0	1	\$21	\$22	\$8	\$14	0.6	105
* All:	TOTALS	9,715	2.0	-1	\$1,306	\$7,229	\$1,101	\$6,128	4.7	9,538

^{* -} All incentives presented in this table are included as placeholders for planning purposes and are based on previously run state rebate programs. Contact your utility provider for details on current programs.

Figure 7 – Cost Effective ECMs

^{** -} Simple Payback Period is based on net measure costs (i.e. after incentives).

^{** -} Simple Payback Period is based on net measure costs (i.e. after incentives).





4.1 Lighting

#	Energy Conservation Measure		Peak Demand Savings (kW)		Annual Energy Cost Savings (\$)	Estimated M&L Cost (\$)	Estimated Incentive (\$)*	Estimated Net M&L Cost (\$)		CO ₂ e Emissions Reduction (Ibs)
Lighting Upgrades		8,669	1.6	-2	\$1,153	\$4,777	\$778	\$3,999	3.5	8,451
ECM 1	Install LED Fixtures	4,599	0.0	0	\$642	\$2,824	\$300	\$2,524	3.9	4,631
ECM 2	Retrofit Fixtures with LED Lamps	4,070	1.6	-2	\$511	\$1,953	\$478	\$1,475	2.9	3,820

When considering lighting upgrades, we suggest using a comprehensive design approach that simultaneously upgrades lighting fixtures and controls to maximize energy savings and improve occupant lighting. Comprehensive design will also consider appropriate lighting levels for different space types to make sure that the right amount of light is delivered where needed. If conversion to LED light sources is proposed, we suggest converting all of a specific lighting type (e.g., linear fluorescent) to LED lamps to minimize the number of lamp types in use at the facility, which should help reduce future maintenance costs.

ECM 1: Install LED Fixtures

Replace existing fixtures containing halogen incandescent lamps with new LED light fixtures. This measure saves energy by installing LEDs, which use less power than other technologies with a comparable light output.

Maintenance savings may also be achieved since LED lamps last longer than other light sources and therefore do not need to be replaced as often.

Affected Building Areas: exterior fixtures

ECM 2: Retrofit Fixtures with LED Lamps

Replace fluorescent, CFL, or incandescent lamps with LED lamps. Many LED tubes are direct replacements for existing fluorescent tubes and can be installed while leaving the fluorescent fixture ballast in place. LED lamps can be used in existing fixtures as a direct replacement for most other lighting technologies. Be sure to specify replacement lamps that are compatible with existing dimming controls, where applicable. In some circumstances, you may need to upgrade your dimming system for optimum performance.

This measure saves energy by installing LEDs, which use less power than other lighting technologies yet provide equivalent lighting output for the space. Maintenance savings may also be available, as longer-lasting LEDs lamps will not need to be replaced as often as the existing lamps.

Affected Building Areas: all areas with fluorescent fixtures with T8 tubes, CFL, or incandescent lamps





4.2 Lighting Controls

#	Energy Conservation Measure		Peak Demand Savings (kW)		Annual Energy Cost Savings (\$)	Estimated M&L Cost (\$)	Estimated Incentive (\$)*	Estimated Net M&L Cost (\$)		CO ₂ e Emissions Reduction (Ibs)
Lighting	g Control Measures	1,046	0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982
ECM 3	Install Occupancy Sensor Lighting Controls	1,046	0.4	0	\$131	\$2,430	\$315	\$2,115	16.1	982

Lighting controls reduce energy use by turning off or lowering lighting fixture power levels when not in use. A comprehensive approach to lighting design should upgrade the lighting fixtures and the controls together for maximum energy savings and improved lighting for occupants.

ECM 3: Install Occupancy Sensor Lighting Controls

Install occupancy sensors to control lighting fixtures in areas that are frequently unoccupied, even for short periods. For most spaces, we recommend that lighting controls use dual technology sensors, which reduce the possibility of lights turning off unexpectedly.

Occupancy sensors detect occupancy using ultrasonic and/or infrared sensors. When an occupant enters the space, the lighting fixtures switch to full lighting levels. Most occupancy sensor lighting controls allow users to manually turn fixtures on/off, as needed. Some controls can also provide dimming options.

Occupancy sensors can be mounted on the wall at existing switch locations, mounted on the ceiling, or in remote locations. In general, wall switch replacement sensors are best suited to single occupant offices and other small rooms. Ceiling-mounted or remote mounted sensors are used in large spaces, locations without local switching, and where wall switches are not in the line-of-sight of the main work area.

This measure provides energy savings by reducing the lighting operating hours.

Affected Building Areas: offices





4.3 Domestic Water Heating

#	Energy Conservation Measure	Annual Electric Savings (kWh)	Savings		Annual Energy Cost Savings (\$)	Estimated M&L Cost (\$)	Estimated Incentive (\$)*	Estimated Net M&L Cost (\$)		CO ₂ e Emissions Reduction (Ibs)
Domestic Water Heating Upgrade		0	0.0	1	\$21	\$22	\$8	\$14	0.6	105
ECM 4	Install Low-Flow DHW Devices	0	0.0	1	\$21	\$22	\$8	\$14	0.6	105

ECM 4: Install Low-Flow DHW Devices

Install low-flow devices to reduce overall hot water demand. The following low-flow devices are recommended to reduce hot water usage:

Device	Flow Rate			
Faucet aerators (lavatory)	0.5 gpm			
Faucet aerator (kitchen)	1.5 gpm			
Showerhead	2.0 gpm			
Pre-rinse spray valve (kitchen)	1.28 gpm			

Low-flow devices reduce the overall water flow from the fixture, while still providing adequate pressure for washing. Additional cost savings may result from reduced water usage.





5 ENERGY EFFICIENT BEST PRACTICES

A whole building maintenance plan will extend equipment life; improve occupant comfort, health, and safety; and reduce energy and maintenance costs.

Operation and maintenance (O&M) plans enhance the operational efficiency of HVAC and other energy intensive systems and could save 5% –20% of the energy usage in your building without substantial capital investment. A successful plan includes your records of energy usage trends and costs, building equipment lists, current maintenance practices, and planned capital upgrades, and it incorporates your ideas for improved building operation. Your plan will address goals for energy-efficient operation, provide detail on how to reach the goals, and outline procedures for measuring and reporting whether goals have been achieved.

You may already be doing some of these things—see our list below for potential additions to your maintenance plan. Be sure to consult with qualified equipment specialists for details on proper maintenance and system operation.

Energy Tracking with ENERGY STAR Portfolio Manager



You've heard it before—you cannot manage what you do not measure. ENERGY STAR Portfolio Manager is an online tool that you can use to measure and track energy and water consumption, as well as greenhouse gas emissions⁴. Your account has already been established. Now you can continue to keep tabs on your energy performance every month.

Lighting Maintenance



Clean lamps, reflectors and lenses of dirt, dust, oil, and smoke buildup every six to twelve months. Light levels decrease over time due to lamp aging, lamp and ballast failure, and buildup of dirt and dust. Together, this can reduce total light output by up to 60% while still drawing full power.

In addition to routine cleaning, developing a maintenance schedule can ensure that maintenance is performed regularly, and it can reduce the overall cost of fixture re-

lamping and re-ballasting. Group re-lamping and re-ballasting maintains lighting levels and minimizes the number of site visits by a lighting technician or contractor, decreasing the overall cost of maintenance.

Fans to Reduce Cooling Load

Install ceiling fans to supplement your cooling system. Thermostat settings can typically be increased by 4°F with no change in overall occupant comfort due to the wind chill effect of moving air.

AC System Evaporator/Condenser Coil Cleaning

Dirty evaporator and condenser coils restrict air flow and restrict heat transfer. This increases the loads on the evaporator and condenser fan and decreases overall cooling system performance. Keeping the coils clean allows the fans and cooling system to operate more efficiently.

⁴ https://www.energystar.gov/buildings/facility-owners-and-managers/existing-buildings/use-portfolio-manager.





Boiler Maintenance

Many boiler problems develop slowly over time, so regular inspection and maintenance is essential to keeping the heating system running efficiently and preventing expensive repairs. Annual tune-ups should include a combustion analysis to analyze the exhaust from the boilers and to ensure the boiler is operating safely and efficiently. Boilers should be cleaned according to the manufacturer's instructions to remove soot and scale from the boiler heat exchangers to improve heat transfer.

Water Heater Maintenance

The lower the supply water temperature that is used for hand washing sinks, the less energy is needed to heat the water. Reducing the temperature results in energy savings and the change is often unnoticeable to users. Be sure to review the domestic water temperature requirements for sterilizers and dishwashers as you investigate reducing the supply water temperature.

Also, preventative maintenance can extend the life of the system, maintain energy efficiency, and ensure safe operation. At least once a year, follow manufacturer instructions to drain a few gallons out of the water heater using the drain valve. If there is a lot of sediment or debris, then a full flush is recommended. Turn the temperature down and then completely drain the tank. Annual checks should include checks for:

- Leaks or heavy corrosion on the pipes and valves.
- Corrosion or wear on the gas line and on the piping. If you noticed any black residue, soot, or charred metal, this is a sign you may be having combustion issues and you should have the unit serviced by a professional.
- For electric water heaters, look for signs of leaking such as rust streaks or residue around the upper and lower panels covering the electrical components on the tank.
- For water heaters more than three years old, have a technician inspect the sacrificial anode annually.

Water Conservation



Installing dual flush or low-flow toilets and low-flow/waterless urinals are ways to reduce water use. The EPA WaterSense® ratings for urinals is 0.5 gallons per flush (gpf) and for flush valve toilets is 1.28 gpf (this is lower than the current 1.6 gpf federal standard).

For more information regarding water conservation go to the EPA's WaterSense website⁵ or download a copy of EPA's "WaterSense at Work: Best Management Practices

for Commercial and Institutional Facilities" to get ideas for creating a water management plan and best practices for a wide range of water using systems.

Water conservation devices that do not reduce hot water consumption will not provide energy savings at the site level, but they may significantly affect your water and sewer usage costs. Any reduction in water

LGEA Report - Princeton Charter School Marsee Center

⁵ https://www.epa.gov/watersense.

⁶ https://www.epa.gov/watersense/watersense-work-0.





use does however ultimately reduce grid-level electricity use since a significant amount of electricity is used to deliver water from reservoirs to end users.

If the facility has detached buildings with a master water meter for the entire campus, check for unnatural wet areas in the lawn or water seeping in the foundation at water pipe penetrations through the foundation. Periodically check overnight meter readings when the facility is unoccupied, and there is no other scheduled water usage.

Manage irrigation systems to use water more effectively outside the building. Adjust spray patterns so that water lands on intended lawns and plantings and not on pavement and walls. Consider installing an evapotranspiration irrigation controller that will prevent over-watering.

Procurement Strategies

Purchasing efficient products reduces energy costs without compromising quality. Consider modifying your procurement policies and language to require ENERGY STAR or WaterSense products where available.





You don't have to look far in New Jersey to see one of the thousands of solar electric systems providing clean power to homes, businesses, schools, and government buildings. On-site generation includes both renewable (e.g., solar, wind) and non-renewable (e.g., fuel cells) technologies that generate power to meet all or a portion of the facility's electric energy needs. Also referred to as distributed generation, these systems contribute to greenhouse gas (GHG) emission reductions, demand reductions, and reduced customer electricity purchases, which results in improved electric grid reliability through better use of transmission and distribution systems.

Preliminary screenings were performed to determine if an on-site generation measure could be a cost-effective solution for your facility. Before deciding to install an on-site generation system, we recommend conducting a feasibility study to analyze existing energy profiles, siting, interconnection, and the costs associated with the generation project including interconnection costs, departing load charges, and any additional special facilities charges.





6.1 Solar Photovoltaic

Photovoltaic (PV) panels convert sunlight into electricity. Individual panels are combined into an array that produces direct current (DC) electricity. The DC current is converted to alternating current (AC) through an inverter. The inverter is then connected to the building's electrical distribution system.

A preliminary screening based on the facility's electric demand, size and location of free area, and shading elements shows that the facility has no potential for installing a PV array.

This facility does not appear to meet the minimum criteria for a cost-effective solar PV installation. To be cost-effective, a solar PV array needs certain minimum criteria, such as sufficient and sustained electric demand and sufficient flat or south-facing rooftop or other unshaded space on which to place the PV panels.

The graphic below displays the results of the PV potential screening conducted as a part of this audit. The position of each slider indicates the potential (potential increases to the right) that each factor contributes to the overall site potential.




Figure 8 - Photovoltaic Screening





Successor Solar Incentive Program (SuSI)

The SuSI program replaces the SREC Registration Program (SRP) and the Transition Incentive (TI) program. The SuSI program is used to register and certify solar projects in New Jersey. Rebates are not available for solar projects. Solar projects may qualify to earn SREC- IIs (Solar Renewable Energy Certificates-II), however, the project owners *must* register their solar projects prior to the start of construction to establish the project's eligibility.

Get more information about solar power in New Jersey or find a qualified solar installer who can help you decide if solar is right for your building:

Successor Solar Incentive Program (SuSI): https://www.njcleanenergy.com/renewable-energy/programs/susi-program

- Basic Info on Solar PV in NJ: www.njcleanenergy.com/whysolar
- **NJ Solar Market FAQs**: <u>www.njcleanenergy.com/renewable-energy/program-updates-and-background-information/solar-transition/solar-market-faqs</u>.
- Approved Solar Installers in the NJ Market: www.njcleanenergy.com/commercial-industrial/programs/nj-smartstart-buildings/tools-and-resources/tradeally/approved_vendorsearch/?id=60&start=1





6.2 Combined Heat and Power

Combined heat and power (CHP) generates electricity at the facility and puts waste heat energy to good use. Common types of CHP systems are reciprocating engines, microturbines, fuel cells, backpressure steam turbines, and (at large facilities) gas turbines.

CHP systems typically produce a portion of the electric power used on-site, with the balance of electric power needs supplied by the local utility company. The heat is used to supplement (or replace) existing boilers and provide space heating and/or domestic hot water heating. Waste heat can also be routed through absorption chillers for space cooling.

The key criteria used for screening is the amount of time that the CHP system would operate at full load and the facility's ability to use the recovered heat. Facilities with a continuous need for large quantities of waste heat are the best candidates for CHP.

A preliminary screening based on heating and electrical demand, siting, and interconnection shows that the facility has no potential for installing a cost-effective CHP system.

Based on a preliminary analysis, the facility does not appear to meet the minimum requirements for a cost-effective CHP installation. The lack of gas service, low or infrequent thermal load, and lack of space for siting the equipment are the most significant factors contributing to the lack of CHP potential.

The graphic below displays the results of the CHP potential screening conducted as a part of this audit. The position of each slider indicates the potential (potential increases to the right) that each factor contributes to the overall site potential.




Figure 9 - Combined Heat and Power Screening

Find a qualified firm that specializes in commercial CHP cost assessment and installation: http://www.njcleanenergy.com/commercial-industrial/programs/nj-smartstart-buildings/tools-and-resources/tradeally/approved vendorsearch/





7 ELECTRIC VEHICLES (EV)

All electric vehicles (EVs) have an electric motor instead of an internal combustion engine. EVs function by plugging into a charge point, taking electricity from the grid, and then storing it in rechargeable batteries. Although electricity production may contribute to air pollution, the U.S. EPA categorizes allelectric vehicles as zero-emission vehicles because they produce no direct exhaust or tailpipe emissions.

EVs are typically more expensive than similar conventional and hybrid vehicles, although some cost can be recovered through fuel savings, federal tax credit, or state incentives.

7.1 Electric Vehicle Charging

EV charging stations provide a means for electric vehicle operators to recharge their batteries at a facility. While many EV drivers charge at home, others do not have access to regular home charging, and the ability to charge at work or in public locations is critical to making EVs practical for more drivers. Charging can also be used for electric fleet vehicles, which can reduce fuel and maintenance costs for fleets that replace gas or diesel vehicles with EVs.

EV charging comes in three main types. For this assessment, the screening considers addition of Level 2 charging, which is most common at workplaces and other public locations. Depending on the site type

and usage, other levels of charging power may be more appropriate.

The preliminary assessment of EV charging at the facility shows that there is medium potential for adding EV chargers to the facility's parking, based on potential costs of installation and other site factors.


The primary costs associated with installing EV charging are the charger hardware and the cost to extend power from the facility to parking spaces. This may include upgrades to electric panels to serve increased loads.

The type and size of the parking area impact the costs and feasibility of adding EV charging. Parking structure installations can be less costly than surface lot installations as power may be

readily available, and equipment and wiring can be surface mounted. Parking lot installations often require trenching through concrete or asphalt surface. Large parking areas provide greater flexibility in charger siting than smaller lots.

The location and capacity of facility electric panels also impact charger installation costs. A Level 2 charger generally requires a dedicated 208-240V, 40 Amp circuit. The electric panel nearest the planned installation may not have available capacity and may need to be upgraded to serve new EV charging loads. Alternatively, chargers could be powered from a more distant panel. The distance from the panel to the location of charging stations ties directly to costs, as conduits, cables, and potential trenching costs all increase on a per-foot basis. The more charging stations planned, the more likely it is that additional electrical capacity will be needed.

Other factors to consider when planning for EV charging at a facility include who the intended users are, how long they park vehicles at the site, and whether they will need to pay for the electricity they use.







The graphic below displays the results of the EV charging assessment conducted as part of this audit. The position of each slider indicates the impact each factor has on the feasibility of installing EV charging at the site.




Figure 10 - EV Charger Screening

Electric Vehicle Programs Available

New Jersey is leading the way on electric vehicle (EV) adoption on the East Coast. There are several programs designed to encourage EV adoption in New Jersey, which is crucial to reaching a 100% clean energy future.

NJCEP offers a variety of EV programs for vehicles, charging stations, and fleets. Certain EV charging stations that receive electric utility service from Atlantic City Electric Company (ACE) or Public Service Electric & Gas Company (PSE&G), may be eligible for additional electric vehicle charging incentives directly from the utility. Projects may be eligible for both the incentives offered by this BPU program and incentives offered by ACE or PSE&G, up to 90% of the combined charger purchase and installation costs. Please check ACE or PSE&G program eligibility requirements before purchasing EV charging equipment, as additional conditions on types of eligible chargers may apply for utility incentives.

Both Jersey Central Power & Light (JCP&L) and Rockland Electric (RECO) have filed proposals for EV charging programs. BPU staff is currently reviewing those proposals.

For more information and to keep up to date on all EV programs please visit https://www.njcleanenergy.com/commercial-industrial/programs/electric-vehicle-programs





8 PROJECT FUNDING AND INCENTIVES

Ready to improve your building's performance? New Jersey's Clean Energy Programs and Utility Energy Efficiency Programs can help. Pick the program that works best for you. This section provides an overview of currently available incentive programs in.





Program areas staying with NJCEP:

- New Construction (residential, commercial, industrial, government)
- · Large Energy Users
- · Combined Heat & Power & Fuel Cells
- · State Facilities
- Local Government Energy Audits
- · Energy Savings Improvement Program
- Solar & Community Solar





8.1 Utility Energy Efficiency Programs

The Clean Energy Act, signed into law by Governor Murphy in 2018, requires New Jersey's investor-owned gas and electric utilities to reduce their customers' use by set percentages over time. To help reach these targets the New Jersey Board of Public Utilities approved a comprehensive suite of energy efficiency programs to be run by the utility companies.

Prescriptive and Custom

The Prescriptive and Custom rebate program through your utility provider offers incentives for installing prescriptive and custom energy efficiency measures at your facility. This program provides an effective mechanism for securing incentives for energy efficiency measures installed individually or as part of a package of energy upgrades. This program serves most common equipment types and sizes.

Equipment Examples

Lighting
Lighting Controls
HVAC Equipment
Refrigeration
Gas Heating
Gas Cooling
Commercial Kitchen Equipment
Food Service Equipment

Variable Frequency Drives
Electronically Commutate Motors
Variable Frequency Drives
Plug Loads Controls
Washers and Dryers
Agricultural
Water Heating

The Prescriptive program provides fixed incentives for specific energy efficiency measures. Prescriptive incentives vary by equipment type. The Custom program provides incentives for more unique or specialized technologies or systems that are not addressed through prescriptive incentives.

Direct Install

Direct Install is a turnkey program available to existing small to medium-sized facilities with an average peak electric demand that does not exceed 200 kW or less over the recent 12-month period. You work directly with a pre-approved contractor who will perform a free energy assessment at your facility, identify specific eligible measures, and provide a clear scope of work for installation of selected measures. Energy efficiency measures may include lighting and lighting controls, refrigeration, HVAC, motors, variable speed drives, and controls

Incentives

The program pays up to 70% of the total installed cost of eligible measures.

How to Participate

To participate in Direct Install, you will work with a participating contractor. The contractor will be paid the measure incentives directly by the program, which will pass on to you in the form of reduced material and implementation costs. This means up to 70% of eligible costs are covered by the Direct Install program, subject to program rules and eligibility, while the remaining percent of the cost is paid to the contractor by the customer.





Engineered Solutions

The Engineered Solutions Program provides tailored energy-efficiency assistance and services to municipalities, universities, schools, hospitals and healthcare facilities (MUSH), non-profit entities, and multifamily buildings. Customers receive expert guided services, including investment-grade energy auditing, engineering design, installation assistance, construction administration, commissioning, and measurement and verification (M&V) services to support the implementation of cost-effective and comprehensive efficiency projects. Engineered Solutions is generally a good option for medium to large sized facilities with a peak demand over 200 kW looking to implement as many measures as possible under a single project to achieve deep energy savings. Engineered Solutions has an added benefit of addressing measures that may not qualify for other programs. Many facilities pursuing an Energy Savings Improvement Program loan also use this program. Incentives for this program are based on project scope and energy savings achieved.

For more information on any of these programs, contact your local utility provider or visit https://www.njcleanenergy.com/transition.





8.2 New Jersey's Clean Energy Programs

Save money while saving the planet! New Jersey's Clean Energy Program is a statewide program that offers incentives, programs, and services that benefit New Jersey residents, businesses, educational, non-profit, and government entities to help them save energy, money, and the environment.

Large Energy Users

The Large Energy Users Program (LEUP) is designed to foster self-directed investment in energy projects. This program is offered to New Jersey's largest energy customers that annually contribute at least \$200,000 to the NJCEP aggregate of all buildings/sites. This equates to roughly \$5 million in energy costs in the prior fiscal year.

Incentives

Incentives are based on the specifications below. The maximum incentive per entity is the lesser of:

- \$4 million
- 75% of the total project(s) cost
- 90% of total NJCEP fund contribution in previous year
- \$0.33 per projected kWh saved; \$3.75 per projected Therm saved annually

How to Participate

To participate in LEUP, you will first need submit an enrollment application. This program requires all qualified and approved applicants to submit an energy plan that outlines the proposed energy efficiency work for review and approval. Applicants may submit a Draft Energy Efficiency Plan (DEEP), or a Final Energy Efficiency Plan (FEEP). Once the FEEP is approved, the proposed work can begin.

Detailed program descriptions, instructions for applying, and applications can be found at www.njcleanenergy.com/LEUP.





Combined Heat and Power

The Combined Heat & Power (CHP) program provides incentives for eligible CHP or waste heat to power (WHP) projects. Eligible CHP or WHP projects must achieve an annual system efficiency of at least 65% (lower heating value, or LHV), based on total energy input and total utilized energy output. Mechanical energy may be included in the efficiency evaluation.

Incentives

Eligible Technologies	Size (Installed Rated Capacity) ¹	Incentive (\$/kW)	% of Total Cost Cap per Project ³	\$ Cap per Project ³	
Powered by non- renewable or renewable fuel source ⁴	≤500 kW	\$2,000	30-40% ²	\$2 million	
Gas Internal Combustion Engine	>500 kW - 1 MW	\$1,000			
Gas Combustion Turbine	> 1 MW - 3 MW	\$550			
Microturbine Fuel Cells with Heat Recovery	>3 MW	\$350	30%	\$3 million	
Waste Heat to	<1 MW	\$1,000	30%	\$2 million	
ower*	> 1MW	\$500	50 /6	\$3 million	

^{*}Waste Heat to Power: Powered by non-renewable fuel source, heat recovery or other mechanical recovery from existing equipment utilizing new electric generation equipment (e.g. steam turbine).

Check the NJCEP website for details on program availability, current incentive levels, and requirements.

How to Participate

You will work with a qualified developer or consulting firm to complete the CHP application. Once the application is approved the project can be installed. Information about the CHP program can be found at www.njcleanenergy.com/CHP.





Successor Solar Incentive Program (SuSI)

The SuSI program replaces the SREC Registration Program (SRP) and the Transition Incentive (TI) program. The program is used to register and certify solar projects in New Jersey. Rebates are not available for solar projects, but owners of solar projects *must* register their projects prior to the start of construction to establish the project's eligibility to earn SREC-IIs (Solar Renewable Energy Certificates-II). SuSI consists of two subprograms. The Administratively Determined Incentive (ADI) Program and the Competitive Solar Incentive (CSI) Program.

Administratively Determined Incentive (ADI) Program

The ADI Program provides administratively set incentives for net metered residential projects, net metered non-residential projects 5 MW or less, and all community solar projects.

After the registration is accepted, construction is complete, and a complete final as-built packet has been submitted, the project is issued a New Jersey certification number, which enables it to generate New Jersey SREC- IIs.

Market Segments	Size MW dc	Incentive Value (\$/SREC II)	Public Entities Incentive Value - \$20 Adder (\$/SRECII)
Net Metered Residential	All types and sizes	\$90	N/A
Small Net Metered Non-Residential located on Rooftop, Carport, Canopy and Floating Solar	Projects smaller than 1 MW	\$100	\$120
Large Net Metered Non-Residential located on Rooftop, Carport, Canopy and Floating Solar	Projects 1 MW to 5 MW	\$90	\$110
Small Net Metered Non-Residential Ground Mount	Projects smaller than 1 MW	\$85	\$105
Large Net Metered Non-Residential Ground Mount	Projects 1 MW to 5 MW	\$80	\$100
LMI Community Solar	Up to 5 MW	\$90	N/A
Non-LMI Community Solar	Up to 5 MW	\$70	N/A
Interim Subsection (t)	All types and sizes	\$100	N/A

Eligible projects may generate SREC-IIs for 15 years following the commencement of commercial operations which is defined as permission to operate (PTO) from the Electric Distribution Company. After 15 years, projects may be eligible for a NJ Class I REC.

SREC-IIs will be purchased monthly by the SREC-II Program Administrator who will allocate the SREC-IIs to the Load Serving Entities (BGS Providers and Third-Party Suppliers) annually based on their market share of retail electricity sold during the relevant Energy Year.

The ADI Program online portal is now open to new registrations.

Competitive Solar Incentive Program

The Competitive Solar Incentive (CSI) Program will provide competitively set incentives for grid supply projects and net metered non-residential projects greater than 5MW (dc). The program is currently under development. For updates, please continue to check the <u>Solar Proceedings</u> page on the New Jersey's Clean Energy Program website.

Solar projects help the State of New Jersey reach renewable energy goals outlined in the state's Energy Master

If you are considering installing solar photovoltaics on your building, visit the following link for more information: https://njcleanenergy.com/renewable-energy/programs/susi-program.





Energy Savings Improvement Program

The Energy Savings Improvement Program (ESIP) serves New Jersey's government agencies by financing energy projects. An ESIP is a type of performance contract, whereby school districts, counties, municipalities, housing authorities, and other public and state entities enter into contracts to help finance building energy upgrades. Annual payments are lower than the savings projected from the energy conservation measures (ECMs), ensuring that ESIP projects are cash flow positive for the life of the contract.

ESIP provides government agencies in New Jersey with a flexible tool to improve and reduce energy usage with minimal expenditure of new financial resources. NJCEP incentive programs described above can also be used to help further reduce the total project cost of eligible measures.

How to Participate

This LGEA report is the first step to participating in ESIP. Next, you will need to select an approach for implementing the desired ECMs:

- (1) Use an energy services company or "ESCO."
- (2) Use independent engineers and other specialists, or your own qualified staff, to provide and manage the requirements of the program through bonds or lease obligations.
- (3) Use a hybrid approach of the two options described above where the ESCO is used for some services and independent engineers, or other specialists or qualified staff, are used to deliver other requirements of the program.

After adopting a resolution with a chosen implementation approach, the development of the energy savings plan can begin. The ESP demonstrates that the total project costs of the ECMs are offset by the energy savings over the financing term, not to exceed 15 years. The verified savings will then be used to pay for the financing.

The ESIP approach may not be appropriate for all energy conservation and energy efficiency improvements. Carefully consider all alternatives to develop an approach that best meets your needs. A detailed program descriptions and application can be found at www.njcleanenergy.com/ESIP.

ESIP is a program delivered directly by the NJBPU and is not an NJCEP incentive program. As mentioned above, you can use NJCEP incentive programs to help further reduce costs when developing the energy savings plan. Refer to the ESIP guidelines at the link above for further information and guidance on next steps.





9 PROJECT DEVELOPMENT

Energy conservation measures (ECMs) have been identified for your site, and their energy and economic analyses are provided within this LGEA report. Note that some of the identified projects may be mutually exclusive, such as replacing equipment versus upgrading motors or controls. The next steps with project development are to set goals and create a comprehensive project plan. The graphic below provides an overview of the process flow for a typical energy efficiency or renewable energy project. We recommend implementing as many ECMs as possible prior to undertaking a feasibility study for a renewable project. The cyclical nature of this process flow demonstrates the ongoing work required to continually improve building energy efficiency over time. If your building(s) scope of work is relatively simple to implement or small in scope, the measurement and verification (M&V) step may not be required. It should be noted through a typical project cycle, there will be changes in costs based on specific scopes of work, contractor selections, design considerations, construction, etc. The estimated costs provided throughout this LGEA report demonstrate the unburdened turn-key material and labor cost only. There will be contingencies and additional costs at the time of implementation. We recommend comprehensive project planning that includes the review of multiple bids for project work, incorporates potential operations and maintenance (O&M) cost savings, and maximizes your incentive potential.




Figure 11 - Project Development Cycle





10 ENERGY PURCHASING AND PROCUREMENT STRATEGIES

10.1 Retail Electric Supply Options

Energy deregulation in New Jersey has increased energy buyers' options by separating the function of electricity distribution from that of electricity supply. Though you may choose a different company from which to buy your electric power, responsibility for your facility's interconnection to the grid and repair to local power distribution will still reside with the traditional utility company serving your region.

If your facility is not purchasing electricity from a third-party supplier, consider shopping for a reduced rate from third-party electric suppliers. If your facility already buys electricity from a third-party supplier, review and compare prices at the end of each contract year.

A list of licensed third-party electric suppliers is available at the NJBPU website⁷.

10.2 Retail Natural Gas Supply Options

The natural gas market in New Jersey is also deregulated. Most customers that remain with the utility for natural gas service pay rates that are market based and fluctuate monthly. The utility provides basic gas supply service to customers who choose not to buy from a third-party supplier for natural gas commodity.

A customer's decision about whether to buy natural gas from a retail supplier typically depends on whether a customer prefers budget certainty and/or longer-term rate stability. Customers can secure longer-term fixed prices by signing up for service through a third-party retail natural gas supplier. Many larger natural gas customers may seek the assistance of a professional consultant to assist in their procurement process.

If your facility does not already purchase natural gas from a third-party supplier, consider shopping for a reduced rate from third-party natural gas suppliers. If your facility already purchases natural gas from a third-party supplier, review and compare prices at the end of each contract year.

A list of licensed third-party natural gas suppliers is available at the NJBPU website⁸.

⁷ www.state.nj.us/bpu/commercial/shopping.html.

⁸ www.state.nj.us/bpu/commercial/shopping.html.





APPENDIX A: EQUIPMENT INVENTORY & RECOMMENDATIONS

Lighting Inventory & Recommendations

<u>Lighting inventor</u>	ting Inventory & Recommendations Existing Conditions							Proposed Conditions								Energy Impact & Financial Analysis						
	EXISTIN	g conditions					РТОРС	Jseu Conditio	ПЪ						Lifetgy impact & Financial Analysis							
Location	Fixture Quantit Y	Fixture Description	Control System	Light Level	Watts per Fixtur e	Annual Operatin g Hours	ECM #	Fixture Recommendation	Add Controls?	Fixture Quantit Y	Fixture Description	Control System	Watts per Fixtur e	Annual Operatin g Hours	Total Peak kW Savings	Total Annual kWh Savings	Total Annual MMBtu Savings	Total Annual Energy Cost Savings	Estimated M&L Cost (\$)	Total Incentives	Simple Payback w/ Incentives in Years	
Assistant to Head of School	4	Linear Fluorescent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	4	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.2	425	0	\$53	\$416	\$75	6.4	
Basement	2	Compact Fluores cent: (1) 26W A19 Screw-In Lamp	Wall Switch	S	26	500	2	Relamp	No	2	LED Lamps : A19 Lamps	Wall Switch	19	500	0.0	8	0	\$1	\$34	\$2	33.5	
CFL Office	6	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	6	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.2	637	0	\$80	\$489	\$95	4.9	
Exterior Flood	6	Halogen Incandescent: (1) 250W Lamp	Photocell	S	250	4,380	1	Fixture Replacement	No	6	LED - Fixtures: Outdoor Wall- Mounted Area Fixture	Photocell	75	4,380	0.0	4,599	0	\$642	\$2,824	\$300	3.9	
Head of School Office	4	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	4	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.2	425	0	\$53	\$416	\$75	6.4	
Main Entrance	1	Compact Fluorescent: (1) 26W A19 Screw-In Lamp	Wall Switch	S	26	2,300	2	Relamp	No	1	LED Lamps: A19 Lamps	Wall Switch	19	2,300	0.0	18	0	\$2	\$17	\$1	7.3	
Main Entrance	2	Compact Fluores cent: (2) 26W A19 Screw-In Lamps	Wall Switch	S	52	2,300	2	Relamp	No	2	LED Lamps: A19 Lamps	Wall Switch	37	2,300	0.0	76	0	\$10	\$69	\$4	6.8	
Main Entrance	1	Exit Signs: LED - 2 W Lamp	None		6	8,760		None	No	1	Exit Signs: LED - 2 W Lamp	None	6	8,760	0.0	0	0	\$0	\$0	\$0	0.0	
Meeting Room	8	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	8	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.3	850	0	\$107	\$562	\$115	4.2	
Rented Area	4	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	4	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.2	425	0	\$53	\$416	\$75	6.4	
Rented Office Space	6	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	6	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.2	637	0	\$80	\$489	\$95	4.9	
Rented Second Floor Office	5	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	5	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.2	531	0	\$67	\$453	\$85	5.5	
Rented Second Floor Office 2	6	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	6	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.2	637	0	\$80	\$489	\$95	4.9	
Rented Second Floor Office 3	3	Linear Fluores cent - T8: 4' T8 (32W) - 2L	Wall Switch	S	62	2,300	2, 3	Relamp	Yes	3	LED - Linear Tubes: (2) 4' Lamps	Occupanc y Sensor	29	1,587	0.1	319	0	\$40	\$380	\$65	7.9	
Restroom	1	Incandes cent: (4) 40W G25 Screw-In Lamps	Wall Switch	S	160	500	2	Relamp	No	1	LED Lamps: G25 Lamps	Wall Switch	24	500	0.1	75	0	\$9	\$101	\$8	9.9	
Second Floor	2	Compact Fluorescent: (1) 26W A19 Screw-In Lamp	Wall Switch	S	26	2,300	2	Relamp	No	2	LED Lamps: A19 Lamps	Wall Switch	19	2,300	0.0	35	0	\$4	\$34	\$2	7.3	
Second Floor Kitchenette	1	Compact Fluorescent: (1) 26W A19 Screw-In Lamp	Wall Switch	S	26	2,300	2	Relamp	No	1	LED Lamps: A19 Lamps	Wall Switch	19	2,300	0.0	18	0	\$2	\$17	\$1	7.3	
Second Floor Restroom	1	LED Lamps: (4) 10W G25 Screw- In Lamps	Wall Switch	S	40	500		None	No	1	LED Lamps: (4) 10W G25 Screw-In Lamps	Wall Switch	40	500	0.0	0	0	\$0	\$0	\$0	0.0	

Local Government Energy Audit – Marsee Center





Packaged HVAC Inventory & Recommendations

W = Within Useful Life

B = Beyond Useful Life

	Existing Conditions									Prop	pposed Conditions Energy Impact & Financial Analysis											
Location	Area(s)/System(s) Served	System Quantit Y		Cooling Capacit y per Unit (Tons)	Heating Capacity per Unit (MBh)	Cooling Mode Efficiency (SEER/IEER/ EER)	Heating Mode Efficiency	Manufacturer	Model	Remaining Useful Life	ECM #	Install High System Efficienc Quantit System Type y y System?	Cooling Capacit y per Unit (Tons)	Capacity	Cooling Mode Efficiency (SEER/IEER/ EER) Heatin Mode Efficience	Total Peak	Total Annual kWh Savings	l Total Annual MMBtu Savings	Total Annual Energy Cost Savings		Total Incentives	Simple Payback w/ Incentives in Years
Rented Area	Rented Area	1	Packaged Terminal HP	2.00	24.00	9.00	2.5 COP	Frigidaire	Unknown	W		No				0.0	0	0	\$0	\$0	\$0	0.0
Assistant to Haf of School	Assistant to Haf of School	1	Window AC	0.42		12.50		LG	LW5016	W		No				0.0	0	0	\$0	\$0	\$0	0.0
CFL Office	CFL Office	1	Window AC	0.50		10.70		GE	Unknown	W		No				0.0	0	0	\$0	\$0	\$0	0.0
Meeting Room	Meeting Room	1	Window AC	0.75		11.50		LG	LW8022ERSM	W		No				0.0	0	0	\$0	\$0	\$0	0.0
Rented Office Space	Rented Office Space	1	Window AC	0.50		10.70		LG	LW6012ER	w		No				0.0	0	0	\$0	\$0	\$0	0.0
Rented Second Floor Office	Rented Second Floor Office	1	Window AC	0.50		10.70		Unknown	Unknown	W		No				0.0	0	0	\$0	\$0	\$0	0.0
Rented Second Floor Office 2	Rented Second Floor Office 2	1	Window AC	0.50		11.30		LG	LW6017R	W		No				0.0	0	0	\$0	\$0	\$0	0.0
Second Floor	Second Floor	1	Window AC	0.50		11.20		GE	AEL06LSQ1	W		No				0.0	0	0	\$0	\$0	\$0	0.0
Rented Second Floor Office 3	Rented Second Floor Office 3	1	Window AC	0.50		11.30		LG	LW6017R	W		No				0.0	0	0	\$0	\$0	\$0	0.0

Space Heating Boiler Inventory & Recommendations

	Existing Conditions					Prop	Proposed Conditions							Energy Impact & Financial Analysis							
Location	Area(s)/System(s) Served	System Quantit Y	System Type	Output Capacity per Unit (MBh)	Manufacturer	Model	Remaining Useful Life		Install High Efficienc y System?	System Quantit y	System Type	Output Capacity per Unit (MBh)		Heating Efficienc y Units	Total Peak kW Savings	Total Annual kWh Savings		Total Annual Energy Cost Savings	M&L Cost	Total Incentives	Simple Payback w/ Incentives in Years
Basement	Marsee Center	1	Forced Draft Steam Boiler	115	Weil-McLain	SGO-5 Series 3	W		No						0.0	0	0	\$0	\$0	\$0	0.0

DHW Inventory & Recommendations

		Existing	g Conditions				Prop	osed Co	nditions					Energy Im	pact & Fina	ancial Anal	ysis			
Location	Area(s)/System(s) Served	System Quantit Y	System Type	Manufacturer	Model	Remaining Useful Life	FCM #	Replace?	System Quantit Y	System Type	Fuel Type	System Efficiency	Efficiency Units		Total Annual kWh Savings		Total Annual Energy Cost Savings	Estimated M&L Cost (\$)		Simple Payback w/ Incentives in Years
Basement	Marsee Center	1	Indirect System	Weil-McLain	SGO-5 Series 3	W		No						0.0	0	0	\$0	\$0	\$0	0.0

Local Government Energy Audit – Marsee Center





Low-Flow Device Recommendations

	Reco	mmed	ation Inputs			Energy Impact & Financial Analysis									
Location	ECM #	Device Quantit y	Device Type	Existing Flow Rate (gpm)	Flow	Total Peak kW Savings	kWh	Total Annual MMBtu Savings	Total Annual Energy Cost Savings	Estimated M&L Cost (\$)	Total Incentives	Simple Payback w/ Incentives in Years			
Meeting Room	4	1	Faucet Aerator (Kitchen)	2.20	1.50	0.0	0	0	\$7	\$7	\$2	0.8			
Second Floor Kitchenette	4	1	Faucet Aerator (Kitchen)	1.80	1.50	0.0	0	0	\$3	\$7	\$2	1.8			
Second Floor Restroom	4	1	Faucet Aerator (Lavatory)	1.80	0.50	0.0	0	0	\$12	\$7	\$4	0.3			

Plug Load Inventory

	Existin	g Conditions				
Location	Quantit y	Equipment Description	Energy Rate (W)	ENERGY STAR Qualified ?	Manufacturer	Model
Rented Office Space	1	Electric Resistance Heater	1,500	No	Lakewood	750
Marsee Center	2	Coffee Machine	800	No	Keurig	Unknown
Marsee Center	10	Desktop	250	No	Dell	Unknown
Marsee Center	3	Laptop	150	Yes	Varied	Varied
Marsee Center	2	Microwave	1,000	No	Varied	Varied
Marsee Center	5	Printer	150	Yes	Varied	Varied
Marsee Center	4	Copier	1,500	Yes	Varied	Varied
Meeting Room	1	Projector	150	No	Mitsubishi	Unknown
Second Floor Kitchenette	2	Refrigerator (Mini)	126	No	Varied	Varied
Meeting Room	1	Toaster Oven	1,500	No	Unknown	Unknown
Marsee Center	2	Water Cooler	125	No	Unknown	Unknown





APPENDIX B: ENERGY STAR STATEMENT OF ENERGY **PERFORMANCE**

Energy use intensity (EUI) is presented in terms of site energy and source energy. Site energy is the amount of fuel and electricity consumed by a building as reflected in utility bills. Source energy includes fuel consumed to generate electricity consumed at the site, factoring in electric production and distribution losses for the region.



ENERGY STAR® Statement of Energy **Performance**

Charter, Marsee Center

Primary Property Type: Office Gross Floor Area (ft²): 3,240

Built: 1850

ENERGY STAR® Score¹

For Year Ending: December 31, 2022 Date Generated: June 13, 2023

1. The ENERGY STAR score is a 1-100 assessment of a building's energy efficiency as compared with similar buildings nationwide, adjusting for climate and business activity.

Property & Contact Information

Property Address Charter, Marsee Center 100 Bunn Drive Princeton, New Jersey 08540

Property Owner Princeton Charter School 100 Bunn Drive Princeton, NJ 08540 (609) 924-0575

Primary Contact Larry Paton 100 Bunn Drive Princeton, NJ 08540 (609) 924-0575 lpatton@princetoncharter.org

Property ID: 25640075

Energy Consumption and Energy Use Intensity (EUI) Site EUI Annual Energy by Fuel National Median Comparison Electric - Grid (kBtu) 88,763 (36%) National Median Site EUI (kBtu/ft2) 59.3 77.2 kBtu/ft2 Fuel Oil (No. 2) (kBtu) 161,239 (64%) National Median Source EUI (kBtu/ft²) 97.5 % Diff from National Median Source EUI 30% Source EUI **Annual Emissions** Total (Location-Based) GHG Emissions 20 127 kBtu/ft2

(Metric Tons CO2e/year)

Signature & Stamp of Verifying Professional

ı (Name	e) verify that the above information	in is true and correct to the	best of my knowledge.
LP Signature:	Date:		
Licensed Professional			
·			
()			

Professional Engineer or Registered Architect Stamp (if applicable)

APPENDIX C: GLOSSARY

TERM	DEFINITION
Blended Rate	Used to calculate fiscal savings associated with measures. The blended rate is calculated by dividing the amount of your bill by the total energy use. For example, if your bill is \$22,217.22, and you used 266,400 kilowatt-hours, your blended rate is 8.3 cents per kilowatt-hour.
Btu	British thermal unit: a unit of energy equal to the amount of heat required to increase the temperature of one pound of water by one-degree Fahrenheit.
СНР	Combined heat and power. Also referred to as cogeneration.
СОР	Coefficient of performance: a measure of efficiency in terms of useful energy delivered divided by total energy input.
Demand Response	Demand response reduces or shifts electricity usage at or among participating buildings/sites during peak energy use periods in response to time-based rates or other forms of financial incentives.
DCV	Demand control ventilation: a control strategy to limit the amount of outside air introduced to the conditioned space based on actual occupancy need.
US DOE	United States Department of Energy
EC Motor	Electronically commutated motor
ECM	Energy conservation measure
EER	Energy efficiency ratio: a measure of efficiency in terms of cooling energy provided divided by electric input.
EUI	Energy Use Intensity: measures energy consumption per square foot and is a standard metric for comparing buildings' energy performance.
Energy Efficiency	Reducing the amount of energy necessary to provide comfort and service to a building/area. Achieved through the installation of new equipment and/or optimizing the operation of energy use systems. Unlike conservation, which involves some reduction of service, energy efficiency provides energy reductions without sacrifice of service.
ENERGY STAR	ENERGY STAR is the government-backed symbol for energy efficiency. The ENERGY STAR program is managed by the EPA.
EPA	United States Environmental Protection Agency
Generation	The process of generating electric power from sources of primary energy (e.g., natural gas, the sun, oil).
GHG	Greenhouse gas gases that are transparent to solar (short-wave) radiation but opaque to long-wave (infrared) radiation, thus preventing long-wave radiant energy from leaving Earth's atmosphere. The net effect is a trapping of absorbed radiation and a tendency to warm the planet's surface.
gpf	Gallons per flush

gpm	Gallon per minute
HID	High intensity discharge: high-output lighting lamps such as high-pressure sodium, metal halide, and mercury vapor.
hp	Horsepower
HPS	High-pressure sodium: a type of HID lamp.
HSPF	Heating seasonal performance factor: a measure of efficiency typically applied to heat pumps. Heating energy provided divided by seasonal energy input.
HVAC	Heating, ventilating, and air conditioning
IHP 2014	US DOE Integral Horsepower rule. The current ruling regarding required electric motor efficiency.
IPLV	Integrated part load value: a measure of the part load efficiency usually applied to chillers.
kBtu	One thousand British thermal units
kW	Kilowatt: equal to 1,000 Watts.
kWh	Kilowatt-hour: 1,000 Watts of power expended over one hour.
LED	Light emitting diode: a high-efficiency source of light with a long lamp life.
LGEA	Local Government Energy Audit
Load	The total power a building or system is using at any given time.
Measure	A single activity, or installation of a single type of equipment, that is implemented in a building system to reduce total energy consumption.
МН	Metal halide: a type of HID lamp.
MBh	Thousand Btu per hour
MBtu	One thousand British thermal units
MMBtu	One million British thermal units
MV	Mercury Vapor: a type of HID lamp.
NJBPU	New Jersey Board of Public Utilities
NJCEP	New Jersey's Clean Energy Program: NJCEP is a statewide program that offers financial incentives, programs and services for New Jersey residents, business owners and local governments to help them save energy, money, and the environment.
psig	Pounds per square inch gauge
Plug Load	Refers to the amount of power used in a space by products that are powered by means of an ordinary AC plug.
PV	Photovoltaic: refers to an electronic device capable of converting incident light directly into electricity (direct current).

SEER	Seasonal energy efficiency ratio: a measure of efficiency in terms of annual cooling energy provided divided by total electric input.
SEP	Statement of energy performance: a summary document from the ENERGY STAR Portfolio Manager.
Simple Payback	The amount of time needed to recoup the funds expended in an investment or to reach the break-even point between investment and savings.
SREC (II)	Solar renewable energy credit: a credit you can earn from the state for energy produced from a photovoltaic array.
T5, T8, T12	A reference to a linear lamp diameter. The number represents increments of $1/8^{\text{th}}$ of an inch.
Temperature Setpoint	The temperature at which a temperature regulating device (thermostat, for example) has been set.
therm	100,000 Btu. Typically used as a measure of natural gas consumption.
tons	A unit of cooling capacity equal to 12,000 Btu/hr.
Turnkey	Provision of a complete product or service that is ready for immediate use.
VAV	Variable air volume
VFD	Variable frequency drive: a controller used to vary the speed of an electric motor.
WaterSense®	The symbol for water efficiency. The WaterSense® program is managed by the EPA.
Watt (W)	Unit of power commonly used to measure electricity use.